

Technical delivery specification

Linear TV, Start Ad & Fast Forward Ad

Container			
Format	MXF (OP1a)	MOV (QuickTime)	MP4 (HD MPEG-4)
Timecode	Start 00:00:00:00	Start 00:00:00:00	Start 00:00:00:00
Video Essence			
Codec	MPEG-2	ProRes 422 HQ	AVC/H264
Resolution	HD 1920x1080	HD 1920x1080	HD 1920x1080
Frame rate	25 fps	25 fps	25 fps
Aspect ratio	16/9	16/9	16/9
Profile@Level	422@High / High@High	High Quality (HQ)	High 4.2
Scan type	Interlaced only	Interlaced only	Interlaced only
Scan order	Top Field First	Top Field First	Top Field First
GOP structure	I frame only		
Bit rate mode	CBR		
Bit rate	50 Mbps	185 Mbps	20 Mbps
Safe Area	EBU R 95	EBU R 95	EBU R 95
Audio Essence			
Codec	PCM	PCM	AAC
Channels	2	2	2
Configuration	1x Stereo	1x Stereo	1x Stereo
Sample rate	48 khz	48 khz	48 khz
Bit depth	24 bits	24 bits	24 bits
Loudness	EBU R128 / -23 LUFS (\pm 1 LU)	EBU R128 / -23 LUFS (\pm 1 LU)	EBU R128 / -23 LUFS (\pm 1 LU)

The media duration is required to be of a whole-numbered second, the fault tolerance is zero frame (e.g. duration of 20 seconds is accepted whereas duration of 20 seconds and 5 frames is refused). The media must contain images for the full-length duration, a leading or a trailing clip are not allowed. Any content that contains mute black frames at the SOM (Start of Media) or EOM (End of Media) will be rejected.

Pause Ad

Format	JPG
Ratio	16:9
Image size	1280x720 px
Resolution	72dpi
Color space	RGB
File size	850kb
Safe Area	First 25px